


Item	G163
Description	LFZ-XY LOUDSPEAKER 2x2.50 (BC/TC) TRANSPARENT
Application	Suitable in dry locations for connections in communication technology. The construction and the materials make particularly suitable it for HOME HI-FI applications as connecting cable for loudspeakers.



Marking

Color * = Lot di Production

Costruzione

Cores / Section		nr x mmq	2 x 2,50
Conductor	Material		Bare Copper (BC) - Tinned Copper (TC)
	Type		Stranded
	Construction	n x mm	75 x 0,20
Insulation	Material		Polyvinylchloride (PVC) TM2 (YM2) Cristal
	Color		Transparent
	Dimension	mm	3,60 x 7,30 ± 0,10
Resistance		Ohm/km	8,00

Weight kg / km 70,0

Technical Data

Peak Operating Voltage		Volt	49 Vac / 110 Vdc
Nominal Voltage U ₀ /U		Volt	300/300
Test Voltage		Volt	2.000
Insulation Resistance		MOhm / km	> 20
Temperature Range	Fixed Installation	°C	- 15 / + 70
Min. Bending Radius	Fixed Installation		10 x Diameter

Standards

Inner Conductor Resistance EN 60228 Cl. 5

Product Manager
(Davide Eng. Bagnacani)

Issued 07/04/2010
Versione 07/04/2010
Print Date 29/01/2019