

# Anemometer



## ► VA8020

### Temperature/Vane anemometer

- Measure m/s, km/h, fpm, mph, kts, Beaufort scale, °C, °F
- Resolution: 0.1m/s , 1fpm, 0.1°C , 0.1°F ,
- Range: 0.4~20m/s , 80~4000fpm
- Sample Rate: 0.5sec
- Operating Temperature: -10~50°C , 14~122°F
- Special function Auto power off; Data hold; MAX and MIN; Backlight
- Dimension: 157 x 60 x 30mm
- Weight: 180g



## ► VA8021

### Temperature/Humidity/ Vane anemometer

- Measure: m/s, km/h, fpm, mph, kts, Beaufort, %RH, td(dew point temperature), °C, °F
- Resolution: 0.1m/s 1fpm; 0.1%RH; 0.1°C , 0.1°F
- Range: 0.4~20m/s, 80~4000fpm; 0~100%RH; -10~50°C , 14~122°F
- Accuracy: ± (2% of reading + 0.3m/s) , ± (2% of reading + 60fpm) ±3%RH (5~95%RH) ±1°C , ±1.8°F
- Special function: Auto power off; Data hold; MAX MIN; Back light; Overload display; Low battery indicator



## ► VA8022

### Temperature/Wind volume/ Vane anemometer

- Measure: m/s, km/h, fpm, mph, kts, Beaufort, °C, °F m<sup>3</sup>/s; m<sup>3</sup>/h; CFM; m<sup>2</sup>; ft<sup>2</sup>
- Resolution: 0.1m/s 1fpm; 0.1°C , 0.1°F ; 1 m<sup>3</sup>/s
- Range: 0.4~20m/s; 0~99999m<sup>3</sup>/s; -10~50°C , 14~122°F
- Accuracy: ±(2% of reading + 0.3m/s) , ±(2% of reading + 60fps) ±1°C , ±1.8°F ±(3% of reading) m<sup>3</sup>/s
- Special function: Auto power off; Data hold; MAX MIN; Back light; Overload display; Low battery indicator



### Accessories included

- Free DC1.5V (AAA) Battery x 3
- Free protect cover
- Free Protective carrying case
- Free Wrist Strap
- User Manual



Calibration

