

Productname : 5-56  
 Ref.Nr.: BDS000240\_3\_20141024 (EN)  
 Creationdate : 24.10.14 Version : 2.1  
 Replaces: BDS000240\_20130628

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

5-56  
 Aerosol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

### 1.3. Details of the supplier of the safety data sheet

CRC Industries Europe bvba  
 Touwslagerstraat 1  
 9240 Zele  
 Belgium  
 Tel.: +32(0)52/45.60.11  
 Fax.: +32(0)52/45.00.34  
 E-mail : hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Laurinkatu 57 A 23 B, 08100 Lohja	+358/(19)32.921	
CRC Industries France	6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303.0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Kryptogatan 14, 431 53 Mölndal	0046/31 706 84 80	0046/31 27 39 91

### 1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

**Physical:** Aerosol, category 2  
 Flammable aerosol.  
 Pressurised container: May burst if heated.

**Health:** Not classified



**Productname :** 5-56 **Creationdate :** 24.10.14 Version : 2.1  
**Ref.Nr.:** BDS000240\_3\_20141024 (EN) **Replaces:** BDS000240\_20130628

**Environment:** Not classified  
**Other hazards :** Repeated exposure may cause skin dryness or cracking.

### Classification according to 67/548/EEC or 1999/45/EC:

FLAMMABLE

**Health:** R66: Repeated exposure may cause skin dryness or cracking.  
**Physical:** FLAMMABLE  
**Environment:** Not classified

### 2.2. Label elements

#### Labelling according to Regulation (EC) No 1272/2008

**Hazard pictogram(s):**



**Signal word:** Warning  
**Hazard statement(s):** H223 : Flammable aerosol.  
H229 : Pressurised container: May burst if heated.  
**Precautionary statement(s):** P102 : Keep out of reach of children.  
P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 : Do not spray on an open flame or other ignition source.  
P251 : Do not pierce or burn, even after use.  
P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
**Supplemental Hazard information:** Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47-8	(926-141-6)	50-75	Xn	65-66	B
mineral oil (IP 346 DMSO extract < 3%)	-	-	10-25	-	-	B
carbon dioxide	124-38-9	204-696-9	1-5	-	-	A,G
sulfonic acids,petroleum,sodium salts	68608-26-4	271-781-5	1-5	Xi	36	
<b>Explanation notes</b>						

**Productname :** 5-56  
**Ref.Nr.:** BDS000240\_3\_20141024 (EN)  
**Creationdate :** 24.10.14 Version : 2.1  
**Replaces:** BDS000240\_20130628

A : substance with Community workplace exposure limit  
 B : substance with national established workplace exposure limit  
 G : exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	01-2119456620-43	64742-47-8	(926-141-6)	50-75	Asp. Tox. 1	H304	B
mineral oil (IP 346 DMSO extract < 3%)		-	-	10-25	-	-	B
carbon dioxide		124-38-9	204-696-9	1-5	Press. Gas	H280	A,G
sulfonic acids,petroleum,sodium salts		68608-26-4	271-781-5	1-5	Skin Irrit. 2, Eye Irrit. 2	H315,H319	
<b>Explanation notes</b>							
A : substance with Community workplace exposure limit							
B : substance with national established workplace exposure limit							
G : exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006							

(\* Explanation phrases : see chapter 16)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Contact with eyes :** If substance has got into eyes, immediately wash out with plenty of water  
 If eye irritation persists: Get medical advice/attention.

**Contact with skin :** Wash with plenty of soap and water.  
 If skin irritation occurs: Get medical advice/attention.

**Inhalation :** IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 Call a POISON CENTER or doctor/physician if you feel unwell.

**Ingestion :** If swallowed do not induce vomiting because of risk of aspiration into the lungs.  
 If aspiration is suspected obtain immediate medical attention

### 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation :** Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness

**Ingestion :** After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.  
 Symptoms : sore throat, abdominal pain, nausea, vomiting

**Skin contact :** May cause irritation.  
 Symptoms : redness and pain

**Eye contact :** May cause irritation.  
 Symptoms : redness and pain

### 4.3. Indication of any immediate medical attention and special treatment needed

**General Advice :** If you feel unwell, seek medical advice (show the label where possible)  
 If symptoms persist always call a doctor



Productname : 5-56  
Ref.Nr.: BDS000240\_3\_20141024 (EN)

Creationdate : 24.10.14 Version : 2.1  
Replaces: BDS000240\_20130628

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

### 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C  
Forms hazardous decomposition products  
CO,CO2

### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water  
In case of fire, do not breathe fumes

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources  
Ensure adequate ventilation  
Wear suitable protective clothing and gloves.

### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses  
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

### 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

### 6.4. Reference to other sections

For further information see section 8

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat and sources of ignition  
Take precautionary measures against static discharges  
Equipment should be earthed  
Use explosion-proof electrical/ventilating/lighting/.../equipment.  
Use only non-sparking tools.  
Do not breathe aerosols or vapours.



**Productname :** 5-56  
**Ref.Nr.:** BDS000240\_3\_20141024 (EN)  
**Creationdate :** 24.10.14 Version : 2.1  
**Replaces:** BDS000240\_20130628

Ensure adequate ventilation  
 Avoid contact with skin and eyes.  
 Wash thoroughly after use  
 Wear protective gloves/protective clothing/eye protection/face protection.

## 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.  
 Keep out of reach of children.

## 7.3. Specific end use(s)

Lubricants

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

Exposure limits :

Hazardous ingredient	CAS-nr.	method	
<b>EU established exposure limits:</b>			
carbon dioxide	124-38-9	TWA	5000 ppm

## 8.2. Exposure controls

<b>Control procedures :</b>	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
<b>Personal protection :</b>	Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation
<b>inhalation :</b>	In case of insufficient ventilation, wear suitable respiratory equipment. Air purifying respirator equipped with organic gas/vapor cartridge (type A or AX)
<b>hands and skin :</b>	Wear suitable protective gloves against chemicals (nitrile)
<b>eyes :</b>	Wear safety goggles.
<b>Environmental protection:</b>	Avoid release to the environment. Collect spillage.

# SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)  
**Apperance : physical state :** CO2 propelled liquid.  
**colour :** Amber.  
**odour :** Salicylate.



**Productname :** 5-56  
**Ref.Nr.:** BDS000240\_3\_20141024 (EN)

**Creationdate :** 24.10.14 Version : 2.1  
**Replaces:** BDS000240\_20130628

**pH :** Not applicable.  
**Boiling point/range :** Not available.  
**Flash point :** 78 °C (Closed Cup)  
**Evaporation rate :** Not available.  
**Explosion limits : upper limit :** Not available.  
**lower limit :** Not available.  
**Vapour pressure :** Not available.  
**Relative density :** 0.82 g/cm<sup>3</sup> (@ 20°C).  
**Solubility in water :** Emulsifies with water  
**Auto-ignition :** > 200 °C  
**Viscosity :** < 7 mPa.s.

## 9.2. Other information

**VOC:** 560 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

### 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

### 10.4. Conditions to avoid

Avoid overheating

### 10.5. Incompatible materials

Strong oxidising agent

### 10.6. Hazardous decomposition products

CO,CO<sub>2</sub>

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Inhalation :** Inhalation of solvent vapours may give rise to nausea, headaches and dizziness



**Productname :** 5-56 **Creationdate :** 24.10.14 Version : 2.1  
**Ref.Nr.:** BDS000240\_3\_20141024 (EN) **Replaces:** BDS000240\_20130628

**Ingestion :** After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.  
**Skin contact :** Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis  
 Repeated exposure may cause skin dryness or cracking.  
**Eye contact :** May cause irritation.

**Toxicological data :**

Hazardous ingredient	CAS-nr.	method	
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47-8	LD50 oral rat	> 5000 mg/kg
		LD50 derm.rabit	> 5000 mg/kg

**SECTION 12: Ecological information****12.1. Toxicity**

Not classified

**Ecotoxicological data:**

Hazardous ingredient	CAS-nr.	method	
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47-8	IC50 algae	1000 mg/l
		LC50 fish	1000 mg/l
		EC50 daphnia	1000 mg/l

**12.2. Persistence and degradability**

No experimental data available

**12.3. Bioaccumulative potential**

No experimental data available

**12.4. Mobility in soil**

Insoluble in water

**12.5. Results of PBT and vPvB assessment**

No information available

**12.6. Other adverse effects**

None



Productname : 5-56  
Ref.Nr.: BDS000240\_3\_20141024 (EN)

Creationdate : 24.10.14 Version : 2.1  
Replaces: BDS000240\_20130628

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Product :** This material and its container must be disposed of in a safe way.  
Do not discharge into drains or the environment, dispose to an authorised waste collection point.

**National regulations :** Disposal should be in accordance with local, state or national legislation

## SECTION 14: Transport information

### 14.1. UN number

UN-number : 1950

### 14.2. UN proper shipping name

Proper shipping name: AEROSOLS

### 14.3. Transport hazard class(es)

Class: 2.1  
ADR/RID - Classification code: 5F

### 14.4. Packing group

Packing group: Not applicable.

### 14.5. Environmental hazards

ADR/RID - Environmentally hazardous: No  
IMDG - Marine pollutant: No  
IATA/ICAO - Environmentally hazardous: No

### 14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)  
IMDG - Ems: F-D, S-U  
IATA/ICAO - PAX: 203  
IATA/ICAO - CAO: 203

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.





