

Microphone cables



Applications: Flexible low capacity microphone cable, with spiral shield, suitable for the realization of audio assembly.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact PE
 Core colours: Orange, Transparent
 Waste filler between conductors
 Shield: Spiral covering 100%
 O.F.C. red copper
 Sheath: PVC
 Sheath colours: Black, Grey
C114: Black, Grey



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C114	2	2 x 0,25 (23 AWG)	8x0,20	1,5	6,0	100	B	4,7



Sheath colours
C260: Red, Yellow, Green, Blue

tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C260	2	2 x 0,25 (23 AWG)	8x0,20	1,5	6,0	100	B	4,7

Production on demand



Applications: Extra flex balanced microphone audio cable suitable for realization of audio assembly.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact XLPE
 Core colours: Red, Transparent
 Textile filler between conductors
 Drain wire: O.F.C. tinned copper
 Shield: Spiral covering 100%
 O.F.C. red copper
 Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
T30	2	2 x 24 (0,22 mm ²)	28x0,10	1,1	5,8	100	B	4,5

Conductor Resistance	Capacity Core/core	Capacity Core/shield
Ω/Km ± 5%	pF/mt	pF/mt
90	75	160
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70