

Tantalum capacitors



SRPASSIVES

Capacitor type	tantalum
Tolerance	±20%
Operating temperature	-55...85°C

Symbol	Cap. [μF]	U _{oper.} [V]	Pitch [mm]	Symbol	Cap. [μF]	U _{oper.} [V]	Pitch [mm]
TC-0.1/35	0.1	35	2.54	TC-10/25	10	25	2.54
TC-0.22/35	0.22	35	2.54	TC-10/35	10	35	2.54
TC-0.33/35	0.33	35	2.54	TC-22/6.3	22	6.3	2.54
TC-0.47/35	0.47	35	2.54	TC-22/16	22	16	2.54
TC-0.68/35	0.68	35	2.54	TC-22/25	22	25	2.54
TC-1/35	1	35	2.54	TC-22/35	22	35	5.08
TC-1/50	1	50	2.54	TC-33/16	33	16	2.54
TC-1.5/35	1.5	35	2.54	TC-33/25	33	25	5.08
TC-2.2/25	2.2	25	2.54	TC-33/35	33	35	5.08
TC-2.2/35	2.2	35	2.54	TC-47/6.3	47	6.3	2.54
TC-3.3/16	3.3	16	2.54	TC-47/16	47	16	2.54
TC-3.3/35	3.3	35	2.54	TC-47/25	47	25	5.08
TC-4.7/16	4.7	16	2.54	TC-47/35	47	35	5.08
TC-4.7/25	4.7	25	2.54	TC-68/25	68	25	5.08
TC-4.7/35	4.7	35	2.54	TC-100/6.3	100	6.3	5.08
TC-6.8/35	6.8	35	2.54	TC-100/16	100	16	5.08
TC-10/6.3	10	6.3	2.54	TC-220/6.3	220	6.3	5.08
TC-10/16	10	16	2.54	TC-220/16	220	16	5.08