

Moisture Meter



► VA8040

Building material moisture meter

Specifications

- Parameters: % material moisture content , temperature ,
- Accuracy: Conductivity measurement: $\pm 2\%$ Temperature: $\pm 1^\circ\text{C}$
- Resolution: 0.1% , 0.1°C , 0.1°F
- Measurement range: 0.0%~95.7% , $-10 \sim +50^\circ\text{C}$
- Digital display : 3 digitals.
- Measurement selection:
- Material 1: 8.9~95.7% (Hard wood such as Beech, Spruce, Larch, Birch, Cherry, Walnut and so on)
- Material 2: 7.1~80.0% (Soft wood such as Oak, Pine, Maple, Ash-tree, Douglas fir, Meranti and so on.)
- Material 3: 1.0~2.5% (Cement or Concrete plane, Plaster produce.)
- Material 4: 0.0~3.3% (Anhydrite plane)
- Material 5: 0.7~3.8% (Cement mortar)
- Material 6: 0.5~7.4% (Lime mortar)
- Material 7: 0.0~23.4% (Bricks)



- Ideal for total 7 building materials
- Double display



► VA8043

Wood moisture meter

Features

- Quick measurement of wood moisture.
- LCD display with backlighting.
- Data Hold
- Power AAA * 3

Specification

- Wood moisture range: 0~40% ,
- Resolution : 1% ,
- Accuracy: 2%