

Heat Shrinkable Tubings



RoHS : RoHS

Description :

Heat shrinkable tubings

After shrinkage:1.5x0.40mm

As supplied:3.0x0.18mm

Length:1M

W/approval

Approval:



Feature

Flexible, flame retardant (colors only).

Do not contain organic stannum compound, asbestos, azo compounds and formaldehyde.

Specification

Shrink ratio: 2:1

Operating temperature range: -55°C to 125°C

Shrinking temperature: Start at 70°C

Fully recovery temperature: 120°C

Longitudinal shrink ratio: ≤5%

Item No.		As supplied(mm)		After shrinkage(mm)		Length(M) spool
Black Transparent	Other color	Inside diameter (Min.)	Wall thickness (nominal)	Inside diameter (Max.)	Wall thickness (nominal)	
SL7001	SL7001F	1.0	0.15	0.65	0.28	200
SL70015	SL70015F	1.5	0.18	0.85	0.32	200
SL7002	SL7002F	2.0	0.18	1.00	0.35	200
SL70025	SL70025F	2.5	0.18	1.30	0.38	200
SL7003	SL7003F	3.0	0.18	1.50	0.40	200
SL70035	SL70035F	3.5	0.22	1.80	0.42	200
SL7004	SL7004F	4.0	0.25	2.00	0.45	200
SL7005	SL7005F	5.0	0.25	2.50	0.55	100
SL7006	SL7006F	6.0	0.28	3.00	0.55	100
SL7007	SL7007F	7.0	0.28	3.50	0.55	100
SL7008	SL7008F	8.0	0.28	4.00	0.60	100
SL7009	SL7009F	9.0	0.30	4.50	0.60	100
SL7010	SL7010F	10.0	0.30	5.00	0.60	100
SL7011	SL7011F	11.0	0.30	5.50	0.60	100
SL7012	SL7012F	12.0	0.30	6.00	0.60	100
SL7013	SL7013F	13.0	0.35	6.50	0.65	100
SL7014	SL7014F	14.0	0.35	7.00	0.65	100
SL7015	SL7015F	15.0	0.40	7.50	0.70	100
SL7016	SL7016F	16.0	0.40	8.00	0.70	100
SL7018	SL7018F	18.0	0.40	9.00	0.80	100
SL7020	SL7020F	20.0	0.40	10.00	0.80	100