

PLASTIC SILICON RECTIFIERS

**REVERSE VOLTAGE – 50 to 1000 Volts
FORWARD CURRENT – 3.0 Amperes**


FEATURES

- Low cost
- Diffused junction
- Low forward voltage drop
- Low reverse leakage current
- High current capability

MECHANICAL DATA

- Case: JEDEC DO-201AD, molding compound has UL flammability classification 94V-0
- Polarity: Color band denotes cathode
- Weight: 0.04 ounces, 1.1 grams
- Mounting Position: Any

DO-201AD



DO-201AD		
DIM	MIN	MAX
A	25.4	--
B	7.30	9.50
C	1.20	1.30
D	4.80	5.30
All dimension in millimeter		

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

ABSOLUTE RATINGS

PARAMETER	SYMBOL	1N5400	1N5401	1N5402	1N5403	1N5404	1N5405	1N5406	1N5407	1N5408	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	300	400	500	600	800	1000	V
Maximum DC blocking voltage	V_{DC}	50	100	200	300	400	500	600	800	1000	V
Average rectified output current per device	@ $T_A=55^\circ\text{C}$ $I_{(AV)}$	3.0									A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	@ $T_J=25^\circ\text{C}$ I_{FSM}	200									A
$I^2 t$ rating for fusing (t = 8.3ms)	$I^2 t$	166									A ² S
Operating temperature range	T_J	-55 to +125									°C
Storage temperature range	T_{STG}	-55 to +150									°C

STATIC ELECTRICAL CHARACTERISTICS

PARAMETER	TEST CONDITION		SYMBOL	VALUE	UNIT	
Forward voltage (Note1)	$I_F = 3.0\text{A}$	$T_J = 25^\circ\text{C}$	V_F	1.0	V	
Leakage current	V_R at rated	$T_J = 25^\circ\text{C}$ $T_J = 100^\circ\text{C}$	I_R	10 50	uA	
Typical junction capacitance (Note1)			C_J	50	35	pF

THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	VALUE	UNIT
Typical thermal resistance (Note2)	R_{thJA} R_{thJL} R_{thJC}	30 10 5	°C/W

Note :

- (1) Measured at 1.0MHz and applied reverse voltage of 4.0V DC
- (2) Thermal resistance junction to ambient, lead and case,

RATING AND CHARACTERISTIC CURVES 1N5400 thru 1N5408



FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL JUNCTION CAPACITANCE





FIG.5- TYPICAL REVERSE CHARACTERISTICS



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC. LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.