

Flat telephone cables



Applications:
Flat telephone cable for modular connectors - **RJ 45 4 Pin.**

Characteristics:
Conductors: stranded in O.F.C.
red copper
Cond. insulation: PPE
Core colours: Black, Red, Green, Yellow
External Sheath: PVC
Sheath colours: Black, Grey, White, Ivory

tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C604	4	4 x 28 (0,08 mm ²)	7x0,12	0,9		2,4x4,8	100	B	1,5
							305	B	4,6

Conductor Resistance $\Omega/\text{Km} \pm 5\%$	Impedance $\Omega \pm 5\%$	Max Rated Voltage AC - V
210	100	49
		Operative Temperature °C
		-15 / +70



Applications:
Flat telephone cable for modular connectors - **RJ 45 6 Pin.**

Characteristics:
Conductors: stranded in O.F.C.
red copper
Cond. insulation: PPE
Core colours: White, Black, Red, Green, Yellow, Blue
External Sheath: PVC
Sheath colours: Black, Grey, White, Ivory

tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C606	6	6 x 28 (0,08 mm ²)	7x0,12	0,9		2,4x6,8	100	B	2,1
							305	B	6,3

Conductor Resistance $\Omega/\text{Km} \pm 5\%$	Impedance $\Omega \pm 5\%$	Max Rated Voltage AC - V
210	100	49
		Operative Temperature °C
		-15 / +70



Applications:
Flat telephone cable for modular connectors - **RJ 45 8 Pin.**

Characteristics:
Conductors: stranded in O.F.C.
red copper
Cond. insulation: PPE
Core colours: White, Brown, Yellow, Green, Red, Black, Orange, Blue
External Sheath: PVC
Sheath colours: Black, Grey, White, Ivory

tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C608	8	8 x 28 (0,08 mm ²)	7x0,12	0,9		2,4x8,8	100	B	2,7
							305	B	8,4

Conductor Resistance $\Omega/\text{Km} \pm 5\%$	Impedance $\Omega \pm 5\%$	Max Rated Voltage AC - V
210	100	49
		Operative Temperature °C
		-15 / +70