

Printview: Male header (for PCBs); Straight solder pin 0.8 x 0.8 mm; 2-pole; Pin spacing 2.5 mm / 0.098 in; 100% protected against mismatching; Vertical PCB mounting; with closed end - Item No.: 733-332



**Male header (for PCBs); Straight solder pin 0.8 x 0.8 mm; 2-pole;
Pin spacing 2.5 mm / 0.098 in; 100% protected against mismatching;
Vertical PCB mounting; with closed end**



Item No.: 733-332

Male header (for PCBs); Straight solder pin 0.8 x 0.8 mm; 2-pole; Pin spacing 2.5 mm / 0.098 in; 100% protected against mismatching; Vertical PCB mounting; with closed end

Marking

RoHS ✓
Compliant

Business data

Supplier	WAGO
Item no.	733-332
GTIN / EAN	4050821035596
Content	1
Order amount	200
Customer item number	

Notes

Item description: 100% protected against mismatching; only mating halves with the same pole number can be connected together Coding option available

Technical data

Miscellaneous

No. of poles	2
Pin spacing	2.5 mm (0.098 in)
Color	light gray

Printview: Male header (for PCBs); Straight solder pin 0.8 x 0.8 mm; 2-pole; Pin spacing 2.5 mm / 0.098 in; 100% protected against mismatching; Vertical PCB mounting; with closed end - Item No.: 733-332


Technical data	
<i>Ratings per</i>	<i>IEC/EN 60664-1</i>
<i>Rated voltage (III / 3) [V]</i>	<i>80 [V]</i>
<i>Rated impulse voltage (III / 3) [kV]</i>	<i>2.5 [kV]</i>
<i>Rated voltage (III/2) [V]</i>	<i>160 [V]</i>
<i>Rated impulse voltage (III / 2) [kV]</i>	<i>2.5 [kV]</i>
<i>Rated voltage (II / 2) [V]</i>	<i>320 [V]</i>
<i>Rated impulse voltage (II / 2) [kV]</i>	<i>2.5 [kV]</i>
<i>Rated current [A]</i>	<i>6 [A]</i>
<i>Number of levels</i>	<i>1</i>
<i>Solder pin length [mm]</i>	<i>4.6 [mm]</i>
<i>Drilled hole diameter (tolerance) [mm]</i>	<i>1.1(+ 0.1) [mm]</i>
<i>Drilled hole diameter [mm] [mm]</i>	<i>1.1 [mm]</i>
<i>Tolerance of drilled hole diameter plus [mm] [mm]</i>	<i>+0.1 [mm]</i>
<i>Material group</i>	<i>I</i>
<i>Insulating material</i>	<i>Polyamide 66 (PA 66)</i>
<i>Flammability class per UL94</i>	<i>V0</i>
<i>Limit temperature range</i>	<i>-60 ... 100 C</i>
<i>Contact material</i>	<i>Electrolytic copper (Ecu)</i>
<i>Contact plating</i>	<i>tin-plated</i>
<i>Fire load [MJ]</i>	<i>0.007 [MJ]</i>
<i>Weight [g]</i>	<i>0.36 [g]</i>
<i>Width</i>	<i>7.5 mm / 0.295 in.</i>
<i>Height</i>	<i>13.5 mm / 0.531 in.</i>
<i>Height from the surface</i>	<i>8.9 mm / 0.35 in.</i>
<i>Depth</i>	<i>7.8 mm / 0.307 in.</i>

Printview: Male header (for PCBs); Straight solder pin 0.8 x 0.8 mm; 2-pole; Pin spacing 2.5 mm / 0.098 in; 100% protected against mismatching; Vertical PCB mounting; with closed end - Item No.: 733-332

Images & drawings



Printview: Male header (for PCBs); Straight solder pin 0.8 x 0.8 mm; 2-pole; Pin spacing 2.5 mm / 0.098 in; 100% protected against mismatching; Vertical PCB mounting; with closed end - Item No.: 733-332



Address

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Telefon: 0571/887-0

Fax: 0571/887-169

<http://www.wago.com>

© WAGO Kontakttechnik GmbH & Co. KG

Technische Änderungen und Irrtümer vorbehalten.