



REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE

RECOMMENDED
CABLE STRIPPING DIM'S

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 3. PHOSPHOR BRONZE PER QQ-B-750
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 5. TEFLON MIL-P-19468

1. CRIMPED FERRULE
HEX CRIMP SIZE .213"
2. CRIMPED CONTACT PIN
HEX CRIMP SIZE .068"

DIMENSIONS ARE IN MILLIMETERS										
5	FERRULE	COPPER	NOTE 2	1	FR-648/533X 127C	UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4	PART NO. T6121A1-NT3G-1-50		APPROVED	DATE 10-11-01'
4	CONTACT PIN	NOTE 3	NOTE 4	1	B74000-B-25/11		CHECKED	DATE 10-11-01'		
3	INSULATOR	NOTE 5	NATURAL	1	B74000-3T-50		DRAWN	DATE 10-11-01'		
2	BODY	NOTE 1	NOTE 2	1	T74000-2		FILE NO.	DRAWING NO.		
1	HOUSING	NOTE 1	NOTE 2	1	B70000-1-46/31		SCALE	3/1	ISSUE	A

Amphenol

TITLE
TNC CRIMP JACK

DRAWING NO.
KJ-T6121A1-NT3G-58CU-50

ITEM NO.