

## Unipolar flexible cables



RoHS  
Conformity

**Applications:**  
Unipolar flexible cable for electronics.

**Characteristics:**  
 Conductor: O.F.C. red copper  
 C130 PVC  
 Insulation: C131 PVC HT 105°  
 Sheath colours: **White, Brown, Green, Yellow, Grey, Pink, Blue, Red, Black, Violet**

tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Nominal section AWG	Cond. Format. mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C130	1	1 x 0,22	24	7x0,20	1,2	200	B	0,7
C131		1 x 0,35	22	11x0,20	1,4 PVC HT 105°	200	B	1,0

*Production on demand*

RoHS  
Conformity

**Applications:**  
Unipolar cable with stiff wire 6/10 in tinned copper for electronics.

**Characteristics:**  
 Conductor: O.F.C. tinned copper  
 Insulation: PVC  
 Sheath colours: **Black, White, Red, Green, Blue, Yellow**

## Unipolar cable with Stiff Wire 6/10



RoHS  
Conformity

Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
90	49	-15 / +70
60	49	-15 / +90

tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Nominal section AWG	Cond. Format. mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C133	1	1 x 0,28	23	1x0,60 (6/10)	1,2	200	B	0,9

**Applications:**  
Unipolar flexible cable for tester and measuring devices.  
Conductor composed of n° 64 of Ø mm. 0,10 copper wires.

**Characteristics:**  
 Conductor: O.F.C. tinned copper  
 Cond. Insulation: PVC  
 Sheath colours: **Black, Red**

## Unipolar flexible cable



RoHS  
Conformity

Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
45	49	-15 / +70

tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Nominal section AWG	Cond. Format. mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C205	1	1 x 0,50	20	64x0,10	2,5	100	B	1,3