

## Crimp tools for non-insulated connectors and terminals on 32-16 AWG wires



FUT.PA-09

**ENGINEER®**

<b>Tool type</b>	for crimping
<b>Length</b>	175 mm
<b>Weight</b>	159 g
<b>Application</b>	non-insulated terminals; terminals

### Features:

- ergonomic pads on handles
- fitted with return spring

Symbol	PA-09
Wire cross section	
- 0,032...0,8mm <sup>2</sup>	x
- 0,08...0,2mm <sup>2</sup>	x
- 0,08...0,33mm <sup>2</sup>	
- 0,13...0,2mm <sup>2</sup>	
- 0,13...0,33mm <sup>2</sup>	
- 0,2...0,33mm <sup>2</sup>	x
- 0,2...0,52mm <sup>2</sup>	x
- 0,33...0,82mm <sup>2</sup>	
- 0,52...1,3mm <sup>2</sup>	
Wire size	
- 20...16AWG	
- 22...18AWG	
- 24...20AWG	x
- 24...22AWG	x
- 26...22AWG	
- 26...24AWG	
- 28...24AWG	x
- 32...28AWG	x
Application	
- NDR-T	
- NS25-T	x
- NS39-T	
- NX1001-TF	x
- NXG-T	x