

Spiral shielded cables



RoHS
Conformity

Applications:
Flexible cable for sound reproduction and electronics.

Characteristics:
Conductor: O.F.C. red copper
Cond. Insulation: PVC
Core colour: Red
Shield: Spiral covering 100% O.F.C. red copper
Sheath: PVC
Sheath colour: Black



| Conductor Resistance | Capacity Core/core | Capacity Core/shield |
|----------------------------|--------------------------|--------------------------|
| $\Omega/\text{Km} \pm 5\%$ | pF/mt | pF/mt |
| 75 | | 460 |
| | Max rated Voltage AC - V | Operative Temperature °C |
| | 49 | -15 / +70 |

RoHS
Conformity

Applications:
Flexible cable for sound reproduction and electronics.

Characteristics:
Conductor: O.F.C. red copper
Cond. Insulation: Compact PE
Core colour: White
Shield: Spiral covering 100% O.F.C. red copper
Sheath: PVC
Sheath colour: Black



| | | |
|----|--------------------------|--------------------------|
| 75 | | 94 |
| | Max rated Voltage AC - V | Operative Temperature °C |
| | 49 | -15 / +70 |

RoHS
Conformity

Applications:
Flexible cables with individually shielded cores for sound reproduction and electronics.

Characteristics:
Conductors: O.F.C. red copper
Cond. Insulation: PVC
Core colours: Black, White, Red, Yellow, Green
Shields: Spiral covering 100% O.F.C. red copper
Sheath: PVC
Sheath colour: Black



| | | |
|-----|--------------------------|--------------------------|
| 130 | 150 | 290 |
| 130 | 150 | 290 |
| 130 | 150 | 370 |
| | Max rated Voltage AC - V | Operative Temperature °C |
| | 49 | -15 / +70 |



| tasker® Code | Cond. number | Nominal section mm² | Cond. Format. mm. | External Core Ø mm. | External Cable Diameter mm. | Reel or Spool (* pag. II) | | |
|--------------|--------------|---------------------|-------------------|---------------------|-----------------------------|---------------------------|---|-----|
| C123 | 1 | 1 x 0,25 (23 AWG) | 8x0,20 | 2,3 | 4,5 | 100 | B | 2,8 |



| tasker® Code | Cond. number | Nominal section mm² | Cond. Format. mm. | External Core Ø mm. | External Cable Diameter mm. | Reel or Spool (* pag. II) | | |
|--------------|--------------|---------------------|-------------------|---------------------|-----------------------------|---------------------------|---|-----|
| C115 | 3 | 3 x 0,14 (26 AWG) | 18x0,10 | 1,3 | 5,0 | 100 | B | 4,0 |
| C116 | 4 | 4 x 0,14 (26 AWG) | 18x0,10 | 1,3 | 5,2 | 100 | B | 4,2 |
| C181 | 5 | 5 x 0,14 (26 AWG) | 18x0,10 | 1,3 | 6,5 | 100 | B | 6,5 |